




# PERIMETER STRIP

TEKCEM PERIMETER STRIP provides a simple way to provide the necessary isolation and movement between a screed and the perimeter structure.



## OVERVIEW

TEKCEM PERIMETER STRIP is designed to provide an expansion absorber at the perimeter of a floating or unbonded screed.

TEKCEM PERIMETER STRIP provides for the movement in a screed and is ideal for use with all under floor heated screeds.

The affixed polythene “skirt” provides an easy way to seal the perimeter by lapping and taping to the polythene or other membrane under the screed.

Perforations in the TEKCEM PERIMETER STRIP allow easy tearing off of the strip to the correct height following screed installation.

## AVAILABLE SIZES & OPTIONS

Height	Thickness	Roll Length	Options
100mm	5mm	50m	2400mm x 550mm
100mm	8mm	50m	24
150mm	8mm	50m	
150mm	10mm	50m	
150mm	10mm	50m	With self adhesive strips

## WARNING

Whilst the information provided in this datasheet is true and accurate to the best of our knowledge, it may contain information which is unsuitable under certain circumstances since materials, site conditions and method of application vary with each application.

TEKCEM LTD cannot be held responsible for any loss or damage due to incorrect use or from the possibility of variations in working conditions and/or workmanship beyond our control. The user alone is responsible for any consequences deriving from the product.

## INSTALLATION CONSIDERATIONS

It is most common to use TEKCEM PERIMETER STRIP for floating and unbonded screed where there is a polythene layer immediately under the screed. It is important, particularly if the screed is a pumpable liquid screed, to ensure that the polythene skirt on the TEKCEM PERIMETER STRIP is lapped over or under this polythene and sealed such that the screed cannot pass between the two.

TEKCEM PERIMETER STRIP can be affixed to walls using the self adhesive pull of strips (when ordered with these). Often the TEKCEM PERIMETER STRIP can be held in place by the thermal insulation or, if needed by taping to the wall. If staples are used to hold the TEKCEM PERIMETER STRIP in place it must be ensured that these are only used above the level of the finished screed.

TEKCEM PERIMETER STRIP noted in the availability table as having self adhesive strips will have these to the back of the strip and the polythene skirt.

## HEALTH AND SAFETY

This product is not classified under the Chemicals Hazard Information and Packaging for Supply Regulations. A Material Safety Data Sheet relating to this product can be obtained from TEKCEM LTD. Please dispose of packaging and waste responsibly.